



Demineralizer, double

Double demineralizer DTPO2N system, compact size, designed to be directly connected to auto-load autoclaves.

Available

SKU: DTP02N

Categories: Water demineralisers

Description

The double demineralizer DTPO2N system is an extremely compact universal demineralizer designed to remove all salts from the water by using special resins.

This system provides a continuous supply of pure water and can be directly connected to auto-load autoclaves.

The DTPO2N demineralizer together with the dispenser gun DSR55 is the ideal option for rinsing the tools or to carry out the water load on the manual load autoclaves.

The system is installed inside the sink furniture.

Universal Tecnomed demineralizers are able to remove dissolved salts in the water.

Columns containing ion exchange resins hold the salts of the net water by leaking demineralized water to a quality that varies from 0.1 us to 30us depending on the amount of salts in the incoming water.

This quality complies with the requirements of the EN13060 standard on the purity of water for the supply of small sterilizers and not only.

- 2 cartridge containers
- 2 empty cartridges
- 1 flow regulator
- 1 key
- 1 bracket
- 1 bucket containing resin (1,2 lt.)

Technical features double demineralizer DTPO2N system



Article Code	DTP02N
Flow	48 l/h
Initial water purity	0.1 ?S
Max. water temperature	30°C
Internal cartridge size (d x h) mm	72,5 x 250
Total footprint (l x w x h) mm	270 x 145 x 335
Net weight	2,5 Kg
Assembly time	30 minutes
Power	230/12 vac
Warranty	24 months