



Ivory Silk Line fiber optic turbine, KaVo coupling, 3-hole spray

Ivory Silk Line fiber optic turbine, standard head, Kavo coupling, 3-hole spray

Available

SKU: T501LK

Categories: High-speed handpieces

Description

The **Ivory Silk Line T501LK dental turbine with KaVo connection** is designed to deliver power, precision and comfort in a single professional instrument. Ideal for clinicians looking for high performance, lightness and optimal visibility of the operating field, it combines reliable operation with high-quality construction.

With a **power output of 23W**, the T501LK turbine ensures effective and consistent cutting performance during clinical procedures. The rotor with **ceramic bearings** provides smooth and quiet rotation, helping to reduce vibration and improve precision during treatment.

Manufactured from **steel and titanium**, the T501LK weighs only **45g**, offering excellent handling and comfortable use even during prolonged treatments. Its compact and balanced design helps reduce operator fatigue and supports precise instrument control.

The **integrated fibre optic system** illuminates the working field with an output of **40.000lux**, improving visibility during treatment and contributing to the quality of the clinical result.

The **Ivory Fast Oil** lubrication system makes maintenance simple and quick, allowing the rotor to be kept correctly lubricated using a single adaptor. This helps reduce repair costs and the risk of maintenance errors.

Compact, powerful and designed to provide consistent performance, the **Ivory Silk Line T501LK dental turbine with KaVo connection** is a professional solution for improving efficiency, operating comfort and precision in the dental practice.

Technical features Dental Turbine Ivory Silk Line KaVo Connection

Type of head	Standard
--------------	----------



Stop mechanism	Push Button
Type of Spray	3 nozzles
Weight	45 gr
Material	Titanium and Steel
Coupling Type	KaVo®
Maximum rotation per minute	345.000
Power	23 watt
Rotor bearings	Ceramics
Optical fiber	Yes
Intensity of Light	More than 40.000 lux
Fast Oil System	Yes
Autoclavable	Yes
Air pressure	2.8
Diameter of the head	12,5 mm
Height of the head	13,1 mm
Drill Diameter	1.59-1.60 mm
Drill Length	10-25 mm
Type of Lubrication	Oil/ Grease