



Tecnomed laboratory turbine with spray, 2-way coupling

Tecnomed laboratory turbine with spray, 2-way coupling, 310000 rpm.

Available

SKU: HCP22P

Categories: Laboratory Turbines

Description

Laboratory turbine with spray 2-way.

Our high speed laboratory handpieces are simple, robust, lightweight and well balanced. They are available in spray and sprayless versions, both of which can maintain high torque without vibrations. Thanks to their extraordinary cutting capacity, these handpieces allow dental technicians to save valuable time in performing a wide range of operations.

These high speed laboratory handpieces are ideal for the precision cutting and finishing of ceramic materials. Perfectly balanced internal parts eliminate all vibration and noise, ensure an extended working life, and make these handpieces extremely efficient. A smooth surface prevents the accumulation of dirt.

The bur is released and locked by a safe and simple mechanism operated by a button at the connector end of the handpiece. This innovative mechanism eliminates the need for fiddly and unhygienic external screws to lock the bur. Rotating the ring at the base of the handpiece gives easy access to the lubrication hole without having to disconnect the air line.

Technical features Laboratory turbine with spray 2-way.

Connector	4 x 6 / 2 x 4 mm tube
spray	Yes
Speed	310000 rpm
Bur locking force	40 N
Bur size	1,6 mm
Bur release	Push



Lubrification required	Yes
Noise level	67 db
Air supply	2,8 bar
Weight in grams	81
Diameter	22 mm
Length	125 mm
Warranty	12 months