



Woodpecker UDS-L ultrasonic scaler, EMS compatible, with external tank

Woodpecker benchtop power scaling unit, with external tank, handpiece and EMS compatible tips

Available from 14/11/2025

SKU: AR602

Categories: Professional Equipment, Tabletop Scalers

Description

Woodpecker UDS-L ultrasonic scaler: Precision and Versatility for Every Treatment

The UDS-L scaler by Woodpecker is the perfect solution to meet the needs of any patient, offering versatility and precision for everyday clinical operations. Designed with an intuitive control panel, it allows easy selection of Scaling, Endo, and Perio modes, ensuring optimal performance in every application.

Equipped with an ergonomic and lightweight handpiece, the UDS-L provides a comfortable grip that minimizes vibration during procedures, enhancing the operator's experience. The smooth surface of the handpiece prevents germ buildup, allowing for easy sterilization in autoclave at 135°C. Additionally, its compatibility with EMS® tips makes the scaler highly versatile and ready for immediate use in a variety of clinical procedures.

Key Features:

- **Ergonomics and comfort:** The lightweight, ergonomic handpiece ensures a secure grip and reduces operator fatigue.
- **Versatile functions:** The microprocessor-controlled panel allows quick selection of Scaling, Endo, and Perio modes.
- EMS® compatibility: The scaler supports EMS® tips, offering a wide range of clinical applications.
- Ease of use: With intuitive intensity and water flow adjustments, the device is simple to operate.

Ideal for: The UDS-L Woodpecker is ideal for dental practices and clinics seeking an efficient and versatile tool suitable for tartar removal as well as endodontic and periodontal procedures.

Choose UDS-L Scaler by Woodpecker from Tecnomed Italia and discover a new level of efficiency and reliability in dental treatments. Optimize your daily work with DTE-Woodpecker solutions, with the assurance and guarantee of Tecnomed Italia's after-sales service.



Technical features Woodpecker UDS-L ultrasonic scaler.

Tip compatibility	Ems®
Coupling compatibility	Ems® cord
Optic fibre	No
Power supply	24VAC-220/240V-50/60Hz
Mains water	yes
Ultrasonic frequency	28kHz +/- 3kHz
Handpiece weight (g)	48 gr
Control unit weight (kg)	0,64
Scaler dimensions (wxlxh)	210 x 125 x 135 mm